

>

>



Product Name: LV-67EC

Manufacturer: Commell

Model Number: CMCOLV-67EC

Intel® Atom™ Processor, Onboard LVDS, VGA, Giga LAN, USB2.0, HD Audio, SATA, CF, PCI, PCIE Mini card & Mini-PCI socket, DC 9V ~ 24V or ATX P/S

Form Factor

CPU	Mini-ITX motherboard Intel® Atom™ D525, 1.80GHz, 1MB cache Package type : Micro-FCBGA (FCBGA559)
Memory	1 x 200-pin DDR2-667 SO-DIMM up to 4.0 GB Support Non-ECC, unbuffered memory only
Chipset	Intel® ICH8M
Real Time Clock	Chipset integrated RTC with onboard lithium battery Generates a system reset internal timer for 1min/sec ~ 255min/sec
Watchdog Timer	ACPI 2.0 compliant, supports power saving mode
Power Management	Intel® integrated extreme GMA 3150 Technology
Integrated Graphics	Up to 384MB shared with system memory
Video Memory	Chipset Integrated 18-bit single channel LVDS
LVDS Interface	3 x SATAII interface with 300MB/s transfer rate
Serial ATA Interface	1 x Compact Flash Type-II, 1 x 44-pin IDE
Solid State Disk	Intel® ICH8M integrated with Realtek ALC888 HD Codec
Audio Interface	2 x Intel® 82583V Gigabit Ethernet controller
LAN Interface	Onboard programmable 8-bit Digital I/O interface
GPIO Interface	1 x PCI slot, 2 x PCIe mini card & 1 x Mini-PCI sockets
Expansion Interface	1 x Audio, 4 x USB2.0, 1 x LVDS, 1 x LCD Inverter, 1 x LPT
Internal I/O Port	3 x RS232, 1 x SMBUS, 1 x IrDA, 1 x GPIO

>

External I/O Port

4 x USB, 2 x RJ45 LAN, 1 x DB15 VGA, 1 x Audio, 1 x SPDIF 1 x RS232/422/485, 2 x RS232, , 1 x PS2 keyboard/mouse

Power Requirement

DC 9V ~ 24V input or standard 20-pin ATX power supply

Board Dimension

170mm x 170mm

Temperature

Operating within 0~60 centigrade
Storage within -20~85 centigrade

Specifications

Ce produit a ete rajouté a notre catalogue le mardi 07 février 2012