



Product Name: Carte mère Commell LV679 Alim DC 2 x DVI

Manufacturer: Commell

Model Number: CMCOLV-679D2C

Intel® Core™ 2 Duo (Merom)processor @ 800 MHz FSB

Intel® GME965 & ICH8M , DDRII 533 / 667 MHz up to 3.0 GB ,

Onboard VGA , 2 x DVI , TV-out , 24-bit Dual Channel LVDS .

2 x Mini-PCI and 1 x PCI slot onboard

Onboard 2 x Intel® Gigabit LAN , 7.1 channel HD Audio

RS232/422/485 , IEEE1394 , SPDIF , USB 2.0 ,

8-bit GPIO , LPT , FDD , IrDA , CompactFlash socket

9V ~ 24V Full range DC input or standard 20-pin ATX power supply

Form Factor

Mini-ITX Motherboard (170 x 170 mm)

CPU

Intel® Core™ 2 Duo Merom with Socket P @ 800 MHz FSB

Memory

2 x DDR2 533/667 MHz SODIMM up to 3.0 GB

Chipset

Intel® GME965 & ICH8M

Real Time Clock

Chipset integrated RTC with onboard lithium battery

Watchdog Timer

Generates a system reset internal timer for 1sec/min ~ 255 sec/min

Power Management

ACPI 1.0 compliant, supports power saving mode

PCI Enhanced IDE

1 x Ultra ATA/33 IDE channel up to 2 ATAPI devices

VGA Interface

Intel® GME965 integrated GMA (Graphic Media Accelerator) X3100 Technology

Video Memory

Up to 384 MB shared with system memory

Serial ATA Interface

3 x Serial ATA II Interface with 300 MB/s transfer rate.

>

Audio Interface	Realtek ALC888 HD Audio
LAN Interface	2 x Intel® 82573L Gigabit Ethernet
Solid State Disk	IDE1 supports 44-pin DiskOnModule +5V power supplyCompactFlash Type-II on the solder side.(CompactFlash shared with IDE bus)
GPIO Interface	Onboard programmable 8-bit digital I/O interface
Extend Interface	1 x PCI slot & 2 x Min-PCI socket
External I/O Port	2 x RJ45 LAN ports, 1 x DB15 VGA port,1 x PS/2 Keyboard / Mouse ports, 2 x IEEE 1394 ports, 4 x USB 2.0 ports, Audio, SPDIF, 1 x COM
Internal I/O Port	1 x RS232/422/485, 1 x silm FDD, 1 x IrDA , 1 x LPT 4 x USB 2.0, 1 x 8-bit GPIO, 1 x Audio, 1 x CDIN LVDS and LCD inverter connector, 2 x DVI, 1 x TV-out
Power Requirement	Standard 20-pin ATX power supply or 9V ~ 24V full range DC input (8 ~ 30V is operative)
Board Dimension	170mm x 170 mm (L x W)
Operation Temperature	0 ~ 60°C (32 ~ 140°F)
LV-679D2C	Same as above, but with 2 x DVI interface and CompactFlash socket on the solder side.
LV-679D	Intel® Core™ 2 Duo Mini-ITX Motherboard with onboard VGA, LAN, SATA, USB 2.0 ports Audio, IEEE1394, RS232/422/485, Min-PCI, PCI, LVDS, 1 x DVI interface

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011