

>



Product Name: Carte mere Commell FS-A72G
Manufacturer: Commell
Model Number: CMCOFS-A72G

Intel® Core™ 2 Duo / Core™ 2 Quad processor, 800/1066/1333MHz FSB

Intel® Q45 & ICH10DO chipset, DDRIII 800/1066MHz up to 4GB,
Onboard VGA, Onboard 2 x Intel® Gigabit LAN, 6 x SATA with RAID 0/1/5/10
RS232/422/485, USB 2.0, 8-bit GPIO, LPT, FDD, IrDA

Form Factor

CPU

Memory

Chipset

Real Time Clock

Watchdog Timer

Power Management

VGA Interface

Video Memory

Serial ATA Interface

Audio Interface

LAN Interface

GPIO Interface

Expansion Interface

External I/O Port

PICMG 1.3 Full-size CPU card
Intel® Core™ 2 Quad, Core™ 2 Duo, Celeron®
processor Package type : LGA775 FSB :
800/1066/1333MHz
2 x DDR3 800/1066MHz SDRAM up to 4GB
Intel® Q45 Express & ICH10DO
Chipset integrated RTC with onboard lithium battery
Generates a system reset internal timer for 1sec/min ~
255 sec/min
ACPI 1.0 compliant, supports power saving mode w/ ATX
PSU
Intel® integrated extreme GMA 4500 technology
Up to 1024 MB shared with system memory
6 x Serial ATA II Interface with 300 MB/s transfer
rateSupport RAID 0, 1, 5, 10 and Intel® Matrix Storage
Technology
Realtek ALC888 HD Audio
2 x Intel® 82574L Gigabit Ethernet
Onboard programmable 8-bit digital I/O interface
Support one x16 PCIeSupport one x4 PCIe or four x1
PCIe (Optional)Support four PCI bus master, four
USB2.0 interface
DB15 VGA port, RJ45 LAN port, PS/2 Keyboard/Mouse
port

>

Internal I/O Port	5 x RS232, 1 x RS232/422/485, 1 x LPT, 1 x FDD, 1 x GPIO1 x IrDA, 8 x USB2.0, 1 x SMBus, 1 x Front Audio, 1 x CDIN
Power Requirement	+5V, +12V & 5VSB
Board Dimension	338mm x 126 mm (L x W)
Operation Temperature	0 ~ 60°C (32 ~ 140°F)
FS-A72G	PICMG 1.3 SBC supports Intel® Core™ 2 Quad with onboard VGA, SATA, USB 2.0, HD Audio, RS232/422/485, 1 x Giga LAN Support one x16 PCIe, four x1 PCIe

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011