

>



Product Name: LE-374X

Manufacturer: Commell

Model Number: CMCOLE-374X

Intel® Atom™ N270 processor @ 533 MHz FSB

Intel® 945GSE & ICH7M chipset

DDR2 up to 2.0 GB , DVI , LVDS and HDTV

Intel® Giga LAN , SATA , USB2.0 , COM

CompactFlash and Mini-PCI socket , Audio

DC 9V ~ 24V inputs

Specifications

Form Factor

3.5" Miniboard (146 x 101 mm)

CPU

Intel® Atom N270 (1.6 GHz) @ 533 MHz FSB

Memory

1 x DDR2 SO DIMM support 400/533 MHz up to 2.0 GB

Chipset

Intel® 945GSE & ICH7M

Real Time Clock

Chipset integrated RTC with onboard lithium battery

Watchdog Timer

Generates a system reset internal timer for 1sec/min ~ 255 sec/min

Power Management

ACPI 1.0 compliant, supports power saving mode

VGA Interface

Intel® 945GSE integrated GMA 950 Technology

LVDS Interface

18-bit dual channel LVDS interface

DVI Interface

Onboard DVI Transmitter for DVI interface

Serial ATA Interface

2 x Serial ATA II Interface with 150 MB/s transfer rate.

PCI Enhanced IDE

1 x Ultra ATA/33 IDE channel up to 2 ATAPI devices

Solid State Disk

IDE supports 44-pin DiskOnModule +5V power supply CompactFlash Type-II .

Audio Interface

Realtek ALC655 5.1ch Audio

LAN Interface

1 x Intel® 82574L Gigabit Ethernet

GPIO Interface

Onboard programmable 8-bit digital I/O interface

>

Extend Interface	Min-PCI socket
External I/O Port	1 x RJ45 LAN , 1 x PS/2 Keyboard / Mouse , 2 x USB , 1 x VGA , 1 x COM
Internal I/O Port	1 x RS232/422/485, 1 x IrDA , 2 x USB 2.0, 1 x 8-bit GPIO, 1 x Audio, 1 x CDIN, LVDS and LCD inverter connector, 1 x HDTV
Power Requirement	Full range DC 9V ~ 24V input (8 ~ 30V is operative)
Board Dimension	146mm x 101mm (L x W)
Operation Temperature	0 ~ 60°C (32 ~ 140°F)
LE-374X	Intel® Atom 3.5" Miniboard with onboard VGA, with 24-bit LVDS, HDTV, LAN, SATA, USB 2.0 ports Audio, RS232/422/485, audio, Min-PCI, CompactFlash socket

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011