



Product Name: Carte mere Commell LV-66AX

Manufacturer: Commell

Model Number: CMCOLV-66AX

Mini-ITX VIA C7 Embedded Motherboard

VIA CN896 and VT8251 Chipset

DDR2 up to 4.0 GB, Onboard VGA and optional LVDS or DVI interface

2 x Gigabit LAN, 4 x SATA with RAID function

Mini-PCI and PCI slot , Optional CompactFlash socket

2 x serial ports, 8 x USB 2.0, LPT, FDD, GPIO, HD Audio

- **Form Factor: Mini-ITX with 6.7 x 6.7 inches (17 x 17cm) of dimension**
- **CPU: Onboard embedded VIA C7 1.5 GHz CPU**
- **DRAM: 2 x 240-pin DDR2 400/533/667 SDRAM up to 4.0 GB**
- **Chipset: VIA CN896 and VT8251**
- **PCI Enhanced IDE: UltraATA IDE channels up to 4 ATAPI. (1 x 40-pin & 1 x 44-pin)**
- **External I/O Ports: 1x PS/2 keyboard and mouse, 2 x LAN, 6 x USB, 1 x COM, 1 x VGA, 1 x HD Audio, 1 x SPDIF**
- **Internal I/O Ports: 1 x RS232/422/485, 1 x LPT, 1 x IrDA, 1 x GPIO, 1 x Audio, 1 x FDD, 1 x LVDS or DVI, 2 x USB**
- **DVI Interface: Optional onboard DVI interface (LV-66AD)**
- **LVDS Interface: Optional 18/24-bit LVDS interface (LV-66AX)**
- **Serial ATA: 4 x SATA with 300 MB/s transfer rate with RAID 0/1/0+1/5**
- **Audio: Realtek ALC888 7.1 channel HD codec**
- **GPIO Interface: Onboard programmable 8-bit Digital I/O interface.**
- **LAN Interface: 2 x Realtek 8111C Giga Ethernet controller (LV-66AX & LV-66AD only)**

>

- SSD: IDE support 44-pin DOM with +5V power supply, and CompactFlash Type-II socket in the rear side (Optional)
- Watchdog Timer: Winbond W83697UF with system generates 256 level reset
- Expansive Interface: 1 x Slim PCI slot , 1 x Mini-PCI
- Power Requirement: Standard 20-pin ATX power supply

LV-66AX

Mini-ITX Embedded with EBGA VIA C7 1.5 GHz CPU,
VGA, SATA, Dual LAN, HD Audio, PCI & Mini-PCI,
LVDS interface

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011