Product Name: POC-200
Manufacturer: Neousys
Model Number: BBNEPOC-200

PC Industriel Atom Fanless, durci avec alimentation 12v (de 8 à 55 volts)
Ce mini pc est adapté aux environnements exigeants et aux systemes embarqués (bateaux). Grace a ses deux ports réseau et sa plage de temperature de fonctionnement étendue, il pourra par exemple être utilisé comme passerelle reseau en exterieur, d'autant plus qu'il integre un slot SIM pour y integrer une option 3G.
Les ports réseau POE vous permettent d'alimenter à partir du PC des Cameras ou un point d'accès WiFi

- Ultra-compact dimensions : 15 cm x 10 cm
- Processeur Intel® Atom™ E3845 Quad-core
- Temperature de fonctionnement de -20 °C à 70 °C
- Fanless (sans ventilateurs)
- Entrée electrique de 8 à 35 Volts
- Deux por ethernet Gigabit POE
- Emplacement pour SSD/HDD 2.5
- 4 ports com
- En stantard, possibilité de montage vertical au mur
- Support rail din en option

System Core	
Processor	Intel® Atom™ Bay Trail-I E3845 Quad-core processor
Graphics	Integrated Intel® HD Graphics
Memory	1x SO-DIMM socket for DDR3L-1333
Panel I/O Interface	
Ethernet	2x Gigabit Ethernet ports by Intel® I210
PoE	IEEE 802.3at (25.5W PSE) (POC-200 only)
Video Port	1x DVI-I connector for both analog RGB and DVI/HDMI outputs
Serial Port	1x software-programmable RS-232/422/485 (COM1) 1x RS-232 (COM2)
USB	3x USB 3.0 ports and 1x USB 2.0 port
Audio	1x Speaker-out

DIO	Optional 4-CH isolated DI + 4-CH isolated DO
Internal I/O Interface	
Serial Port	1x optioanl software-programmable RS-232/422/485 (COM3) 1x optional RS-232 (COM4)
Mini PCIe	1x mini PCI Express slot with USIM socket
Storage Interface	
SATA HDD	1x SATA ports with 2.5” HDD/SSD bracket
Power Supply	
DC Input	Built-in 8~35V DC input
Input Connector	1x 2-pin pluggable terminal block for DC input
Mechanical	
Dimension	149mm (W) x 105 mm (H) x 57 mm (D)
Weight	1.1 kg (including one 2.5” HDD)
Mounting	Wall-mounting (standard) or DIN-Rail mounting (optional)
Environmental	
Operating Temperature	-20°C ~ 70°C with SSD , 100% CPU loading */** -10°C ~ 50°C with HDD, 100% CPU loading */**
StorageTemperature	-40°C ~ 85°C
Humidity	10%~90% , non-condensing
Vibration	Operating, 5 Grms, 5-500 Hz, 3 Axes(w/ SSD, according to IEC60068-2-64)
Shock	Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
EMC	CE/FCC Class A, according to EN 55022 & EN 55024

Specifications

Ce produit a ete rajouté a notre catalogue le lundi 10 mars 2014