

>



Product Name: LEO 3I525D-V4G-000  
Manufacturer: Lex  
Model Number: BBLEO-3I525D-V4G-000

Mini pc multi lan sans ventilateur (Fanless PC) 4 Lan avec Atom D525  
Ce mini pc est idéal si vous devez mettre en œuvre un pare feu, une passerelle, un serveur web qui soit extrêmement silencieux. En effet si vous utilisez une SSD, ce serveur ne fera aucun bruits !!!

Spécifications du Boitier

|                        |                         |
|------------------------|-------------------------|
| Dimension              | 50 H x 240 W x 124 D mm |
| Material               | Aluminum                |
| Color                  | Black                   |
| VESA Mounting (option) | 75 x 75 mm              |
| Weight                 | 1.22 Kgs ( Incl. M/B )  |
| Storage Space          | 2.5" HDD                |

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| CPU type          | Intel Atom D525 1.8 GHz processor (Dual core processor)                                                     |
| MB Chipset        | Intel Atom D525+ ICH8M (82801 HBM)                                                                          |
| Graphics          | Intel Luna Pier Refresh Pineview-D Integrated Graphics Engine<br>Dynamic Video Memory Technology (DVMT 4.0) |
| Memory            | on board DDR3 SDRAM 1GB & 1 x RRD3 SO-DIMM socket (max.2GB)                                                 |
| NAND flash memory | CF Card Type II socket for ATA interface                                                                    |
| SATA              | One SATA ports with independent DMA operation supported                                                     |
| LAN               | 4 x Realtek RLT8111DL 10 / 100 / 1000 Mbps.                                                                 |
| IO function       | COM1 Wafer 5pin (TTL Level)<br>Support PS/2 key board & mouse                                               |

&gt;

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| USB                          | 2 x external USB 2.0 + 6 x internal USB2.0                                           |
| Expansion interface          | 2 x PCIe mini card for PCIe & USB interface                                          |
| Power                        | On board DC +12V±5% convert to +3V/+5V/+12V for system                               |
| Dimension                    | 145 x 102 mm (3.5 inch) (M/B) /<br>0~45°C (2.5" HDD) / 0~50°C (CF card)              |
| System Operating Temperature | Please upgrade the hard drive to industrial grade for better temperature performance |
| Operating Humidity           | 5~95%, non-condensing                                                                |

### Specifications

*Ce produit a ete rajouté a notre catalogue le jeudi 12 janvier 2012*