

>



Product Name: Carte mere Commell FS-A70G2
Manufacturer: Commell
Model Number: CMCOFS-A70G2

Intel® Core™ 2 Duo / Core™ 2 Quad processor, 533/800/1066MHz FSB
Intel® Q965 & ICH8DO chipset, DDRII 533/667/800MHz up to 4GB,
Onboard VGA, Onboard 2 x Intel® Gigabit LAN, 6 x SATA with RAID 0/1/5/10
RS232/422/485, USB 2.0, 8-bit GPIO, LPT, FDD, IrDA, Mini-PCI

Form Factor

CPU

Memory

Chipset

Real Time Clock

Watchdog Timer

Power Management

VGA Interface

Video Memory

Serial ATA Interface

Audio Interface

LAN Interface

GPIO Interface

Extend Interface

External I/O Port

Internal I/O Port

PICMG 1.3 CPU Card

Intel Core™ 2 Duo / Pentium D / Pentium 4 processor
LGA775 @ 533 / 800 / 1066 MHz FSB

2 x DDR2 533/667/800 MHz SDRAM up to 4.0 GB

Intel Q965 & ICH8DO

Chipset integrated RTC with onboard lithium battery

Generates a system reset internal timer for 1min ~ 255 min

ACPI 1.0 compliant, supports power saving mode

Intel Q965 integrated GMA (Graphic Media Accelerator) 3000 Technology

Up to 256MB shared with system memory

6 x Serial ATA Interface with 300 MB/s transfer rate.

support RAID 0/1/5/10 and Intel Matrix Storage Technology

Realtek ALC260 2-channel Audio

2 x Intel 82573L Gigabit Ethernet .(FS-A70G2 Model only)

Onboard programmable 8-bit digital I/O interface

1 x Mini-PCI socket

2x RJ45 LAN port (FS-A70G2 model) , 1x DB15 VGA port, 1 x PS/2 Keyboard / Mouse ports,

1 x RS232 & 1 x RS232/422/485, 1 x FDD, 1 x IrDA , 1 x LPT 6 x USB 2.0, 1 x 8-bit GPIO, 1 x Audio, 1 x CDIN

,

>

Expansion Interface

PICMG 1.3 Interface support 1 x PCI-Express and 1 x 4 or 4 x 1 PCI-Express , 4 PCI bus master, and 4 USB2.0 Interface

Power Requirement

+5V , +12V input & 5VSB Requirement

Board Dimension

338mm x 126 mm (L x W)

Operation Temperature

0 ~ 60 •Ž

FS-A70G2

Intel Core™ 2 Duo PICMG 1.3 with onboard VGA, SATA, USB 2.0, Audio,RS232/422/485, Mini-PCI, 2 x Giga LAN

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011