



Product Name: Carte mere Commell FS-97DDG2
Manufacturer: Commell
Model Number: CMCOFS-97DDG2

Intel® Core™ 2 Duo / Core™ 2 Quad, 800/1066/1333MHz FSB

Intel® Q35 & ICH9DO chipset, DDRII 667/800MHz up to 4.0 GB,
Onboard VGA, Optional DVI or LVDS, 2 x Intel® Gigabit LAN,
6 x SATA with RAID 0/1/5/10, RS232/422/485, USB 2.0, 8-bit GPIO, LPT,
FDD, IrDA, Mini-PCI

Form Factor

CPU	PICMG 1.0 CPU Card Intel® Core™ 2 Quad / Core™ 2 Duo processor LGA775 @ 800 / 1066 / 1333 MHz FSB
Memory	2 x DDR2 667/800 MHz SDRAM up to 4.0 GB
Chipset	Intel® Q35 express chipset & ICH9DO
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset internal timer for 1min ~ 255 min
Power Management	ACPI 1.0 compliant, supports power saving mode
VGA Interface	Intel® Q35 integrated GMA (Graphic Media Accelerator) 3100 Technology
Video Memory	Up to 384 MB shared with system memory
DVI Interface	Optional Chrontel CH7307B DVI transmitter interface
LVDS Interface	Optional Chrontel CH7308 LVDS transmitter interface
Serial ATA Interface	6 x Serial ATA Interface with 300 MB/s transfer rate. support RAID 0/1/5/10 and Intel® Matrix Storage Technology
Audio Interface	Realtek ALC888 2-channel HD Audio
LAN Interface	2 x Intel® 82573L Gigabit Ethernet .(Optional)
GPIO Interface	Onboard programmable 8-bit digital I/O interface
Extend Interface	1 x Mini-PCI socket
External I/O Port	RJ45 LAN port, 1 x DB15 VGA port, 1 x PS/2 Keyboard / Mouse port

>

Internal I/O Port

1 x RS232 & 1 x RS232/422/485, 1 x FDD, 1 x IrDA , 1 x LPT 8 x USB 2.0, 1 x 8-bit GPIO, 1 x Audio, 1 x CDIN , 1x DVI (Optional) , LVDS and LCD inverter connector (Optional)

Power Requirement

+5V , +12V input & 5VSB Requirement

Board Dimension

338mm x 122 mm (L x W)

Operation Temperature

0 ~ 60 •Ž

FS-97DDG2

Intel Core™ 2 Duo PICMG 1.0 with onboard VGA, SATA, USB 2.0, Audio,RS232/422/485, Mini-PCI, 1 x DVI , 2 x Giga LAN

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011