

>



Product Name: LEO 3I270A-000  
Manufacturer: Lex  
Model Number: BBLEO-3I270A-000

Mini pc LEO Fanless avec N270, 2 ports COM, 1LAN

Spécifications du Boitier

|                        |                         |
|------------------------|-------------------------|
| Dimension              | 50 H x 240 W x 124 D mm |
| Material               | Aluminum                |
| Color                  | Black                   |
| VESA Mounting (option) | 75 x 75 mm              |
| Weight                 | 1.22 Kgs ( Incl. M/B )  |
| Storage Space          | 2.5" HDD                |

|                   |                                                                                                     |
|-------------------|-----------------------------------------------------------------------------------------------------|
| CPU type          | Intel Atom N270 1.6GHz processor                                                                    |
| Front Side Bus    | 533 MHz                                                                                             |
| MB Chipset        | Intel 945GSE + ICH7M (82801GBM)                                                                     |
| Graphics          | Integrated with Intel 945GSE<br>Dynamic Video Memory Technology(DVMT 3.0)                           |
| Memory            | On board DDRII module 1GB<br>1x DDRII SODIMM (max. 2GB) (Option)                                    |
| NAND flash memory | Support Compact Flash card type II for ATA interface<br>On board SSD 1/2/4/8GBBytes(Option)         |
| SATA              | Two SATA ports with independent DMA operation supported                                             |
| Audio             | Intel High Definition Audio Specification Rev.1.0 Compliant<br>Line-out / Mic-in / Lline-in support |
| LAN               | 1x Intel 82574L or Realtek RLT8111C 10/100/1000 Mbps                                                |
| IO function       | 2x RS232 + 3x RS232 pin header + 1x RS422/485 pin header                                            |

&gt;

|                       |                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------|
| USB                   | 7x USB 2.0 ( 2 external + 5 internal)                                                                 |
| DIO & WDT             | Hardware digital Input & Output, 8xDI / 8xDO<br>Hardware Watch Dog Timer, 0~255 sec programmable      |
| Expansion interface   | 1x Mini PCI socket for only PCI rev 2.2 interface<br>2x PCIe mini card support USB and PCIe interface |
| Power                 | On board DC +12V±5% convert to +3.3V/+5V/+12V for system                                              |
| Dimension             | 145 x 102 mm (3.5 inch) (MB)<br>50H x 240W x 124D mm(Chassis)                                         |
| Operating Temperature | 0~60°C<br>Please upgrade the hard drive to industrial grade for better temperature performance        |
| Operating Humidity    | 5~95%, non-condensing                                                                                 |

## Specifications

---

*Ce produit a ete rajouté a notre catalogue le jeudi 19 janvier 2012*