

>



Product Name: Carte mere Commell HS-873PXG
Manufacturer: Commell
Model Number: CMCOHS-873PXG

Half-size PISA CPU card, supports Intel® Penryn CPU with FSB up to 1066MHz, Intel® GM45 & ICH9M, DDRIII 800/1066 SO-DIMM up to 8GB
VGA, 18/24-bit dual channel LVDS, 3 x SATAII, HD Audio, 8-bit GPIO, LPT
HDTV, IrDA, PCI Express Mini Card socket, 1 x RS232, 1 x RS232/422/485
DVI (optional), 2 x Intel® Gigabit LAN (optional)

Form Factor

	Half-size PISA CPU Card	
CPU	Mobile Intel® Core™2 Duo with Socket P @ 677/800/1066MHz FSB.	2 x 204-pin DDR3 800/1066MHz SDRAM up to 8GB
Chipset	Intel GM45 and ICH9M	
Real Time Clock	Chipset integrated RTC with onboard lithium battery	
Watchdog Timer	Generates a system reset with internal timer for 1min/s ~ 255min/s	
Power Management	ACPI 2.0 compliant, supports power saving mode	
VGA Interface	Intel integrated extreme GMA 4500MHD (Graphic Media Accelerator) Technology	
LVDS Interface	Onboard 18/24-bit dual channel LVDS connector	
DVI Interface	Onboard DVI transmitter with 26-pin DVI connector	
Serial ATA Interface	3 x serial ATAII interface with 300MB/s transfer rate.	

>

Audio Interface	Intel integrated ICH9-M with Realtek HD Audio.
LAN Interface	2 x Intel 82574L Gigabit Ethernet controllers.
GPIO Interface	Onboard programmable 8-bit Digital I/O interface.
Extend Interface	1 x PCI Express Mini Card socket
External I/O Port	2 x RJ45 LAN port, 1 x DB15 VGA port, 1 x PS/2 Keyboard/Mouse Port(For HS-873PXG2, HS-873PXDG2 only)
1 x RJ45 LAN port, 1 x DB15 VGA port, 1 x PS/2 Keyboard/Mouse Port,1 x DB9 RS232(For HS-873PXG, HS-873PXDG only)	
Internal I/O Port	1 x RS232, 1 x RS232/422/485, 1 x FDD, 1 x GPIO,1 x LPT, 1 x CDIN connector, 6 x USB,1 x Audio connector, 1 x LVDS, 1 x HDTV,1 x IrDA connector, 1 x Onboard 5-pin AT keyboard Port,1 x 5-pin LCD inverter connect,1 x DVI (For HS-873PXDG, HS-873PXDG2 only)
Power Requirement	DC 5V/12V power required, optional 5VSB for ATXOnboard 4-pin power connector & 3-pin ATX connector
Board Dimension	185 mm x 127 mm (L x W)
Temperature	Operating within 0~60°CStorage within -20~85°C

Ce produit a ete rajouté a notre catalogue le lundi 18 avril 2011