



Product Name: Carte mere Commell LV-682S21

Manufacturer: Commell

Model Number: CMCOLV-682S21

Mini-ITX AMD Mobile Turion 64 X2 638-pin Processor

ATI RS690E & SB600 Chipset

2 x 200-pin DDRII 533/667MHz SO-DIMM support up to 4.0 GB

ATI RADEON X-700 based 2D/3D graphics engine

24-bit Dual channel LVDS , DVI connector , Audio

2 x SATA interface , 1 x Mini-PCI and 1 x PCI slot

Dual Giga LAN , 8 x USB 2.0 , 4 x COM , CompactFlash socket

- **Form Factor: 170 x 170 mm**
- CPU: support AMD Mobile Turion 64 X2 / Sempro processor at 638-pin
- Chipset: ATI RS690E & ATI SB600
- Memory: 2 x 200-pin DDRII 533/667 MHz SO-DIMM socket supports up to 4.0 GB
- VGA Interface: built-in ATI RADEON X-1250 based 2D/3D graphics engine
- LVDS Interface: Onboard 24-bit dual channel LVDS , ATX Power only.
- Enhanced IDE: One 44-pin UDMA 33 IDE channel up to 2 ATAPI devices.
- Expansive Slots: 1 x PCI slot and 1 x Mini-PCI socket
- Serial ATA interface: 2 x SATA 2 interface with 300 MB/s transfer rate
- LAN Interface: 2 x Realtek RTL8111B Giga LAN
- Audio: Realtek ALC655 Codec
- External I/O Ports: 1 x RS232 & 1 RS232/422/485, 1 x PS/2 keyboard/Mouse, 4 x USB 2.0, 1 x Audio, 2 x RJ45 LAN ports, 1 x DB15 VGA, 1 x 4-pin DC input connector
- Internal I/O Ports: 2 x serial port, 1 x GPIO, 4 x USB 2.0, 1 x LVDS, 1 x DVI, 1 x 1394
- Power Supply: Standard 20-pin ATX power supply or 4-pin 8 ~ 21V full range DC input

>

LV-682S21 LV-682 with Mobile Sempron 2100+

LV-682

AMD Mobile Turion 64 X2 / Sempron 638-pin Procesor
, ATI RS690E & SB600 chipset , Giga LAN , VGA ,
LVDS , Mini-PCI , USB , COM , SATA

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011