

>



Product Name: Carte mere Commell FS-A72G2
Manufacturer: Commell
Model Number: CMCOFS-A72G2

Intel® Core™ 2 Duo / Core™ 2 Quad processor, 800/1066/1333MHz FSB


Intel® Q45 & ICH10DO chipset, DDRIII 800/1066MHz up to 4GB,
Onboard VGA, Onboard 2 x Intel® Gigabit LAN, 6 x SATA with RAID 0/1/5/10
RS232/422/485, USB 2.0, 8-bit GPIO, LPT, FDD, IrDA

Form Factor	PICMG 1.3 Full-size CPU card
CPU	Intel® Core™ 2 Quad, Core™ 2 Duo, Celeron® processor Package type : LGA775 FSB : 800/1066/1333MHz
Memory	2 x DDR3 800/1066MHz SDRAM up to 4GB
Chipset	Intel® Q45 Express & ICH10DO
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset internal timer for 1sec/min ~ 255 sec/min
Power Management	ACPI 1.0 compliant, supports power saving mode w/ ATX PSU
VGA Interface	Intel® integrated extreme GMA 4500 technology
Video Memory	Up to 1024 MB shared with system memory
Serial ATA Interface	6 x Serial ATA II Interface with 300 MB/s transfer rate Support RAID 0, 1, 5, 10 and Intel® Matrix Storage Technology
Audio Interface	Realtek ALC888 HD Audio
LAN Interface	2 x Intel® 82574L Gigabit Ethernet
GPIO Interface	Onboard programmable 8-bit digital I/O interface
Expansion Interface	Support one x16 PCIeSupport one x4 PCIe or four x1 PCIe (Optional)Support four PCI bus master, four USB2.0 interface
External I/O Port	DB15 VGA port, RJ45 LAN port, PS/2 Keyboard/Mouse port



Internal I/O Port	5 x RS232, 1 x RS232/422/485, 1 x LPT, 1 x FDD, 1 x GPIO1 x IrDA, 8 x USB2.0, 1 x SMBus, 1 x Front Audio, 1 x CDIN
Power Requirement	+5V, +12V & 5VSB
Board Dimension	338mm x 126 mm (L x W)
Operation Temperature	0 ~ 60°C (32 ~ 140°F)
FS-A72G2	PICMG 1.3 SBC supports Intel® Core™ 2 Quad with onboard VGA, SATA, USB 2.0, HD Audio, RS232/422/485, 2 x Giga LAN Support one x16 PCIe, four x1 PCIe

Specifications



Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011