

>



Product Name: Carte mere Commell FS-A72G

Manufacturer: Commell

Model Number: CMCOFS-A72G

Intel® Core™ 2 Duo / Core™ 2 Quad processor, 800/1066/1333MHz FSB

Intel® Q45 & ICH10DO chipset, DDRIII 800/1066MHz up to 4GB,

Onboard VGA, Onboard 2 x Intel® Gigabit LAN, 6 x SATA with RAID 0/1/5/10

RS232/422/485, USB 2.0, 8-bit GPIO, LPT, FDD, IrDA

Form Factor

CPU

PICMG 1.3 Full-size CPU card

Intel® Core™ 2 Quad, Core™ 2 Duo, Celeron®
processor Package type : LGA775 FSB :
800/1066/1333MHz

Memory

2 x DDR3 800/1066MHz SDRAM up to 4GB

Chipset

Intel® Q45 Express & ICH10DO

Real Time Clock

Chipset integrated RTC with onboard lithium battery

Watchdog Timer

Generates a system reset internal timer for 1sec/min ~
255 sec/min

Power Management

ACPI 1.0 compliant, supports power saving mode w/ ATX
PSU

VGA Interface

Intel® integrated extreme GMA 4500 technology

Video Memory

Up to 1024 MB shared with system memory

Serial ATA Interface

6 x Serial ATA II Interface with 300 MB/s transfer
rateSupport RAID 0, 1, 5, 10 and Intel® Matrix Storage
Technology

Audio Interface

Realtek ALC888 HD Audio

LAN Interface

2 x Intel® 82574L Gigabit Ethernet

GPIO Interface

Onboard programmable 8-bit digital I/O interface

Expansion Interface

Support one x16 PCIeSupport one x4 PCIe or four x1
PCIe (Optional)Support four PCI bus master, four
USB2.0 interface


External I/O Port

DB15 VGA port, RJ45 LAN port, PS/2 Keyboard/Mouse
port



Internal I/O Port	5 x RS232, 1 x RS232/422/485, 1 x LPT, 1 x FDD, 1 x GPIO1 x IrDA, 8 x USB2.0, 1 x SMBus, 1 x Front Audio, 1 x CDIN
Power Requirement	+5V, +12V & 5VSB
Board Dimension	338mm x 126 mm (L x W)
Operation Temperature	0 ~ 60°C (32 ~ 140°F)
FS-A72G	PICMG 1.3 SBC supports Intel® Core™ 2 Quad with onboard VGA, SATA, USB 2.0, HD Audio, RS232/422/485, 1 x Giga LAN Support one x16 PCIe, four x1 PCIe

Specifications



Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011