

>



Product Name: LEO 3I525A-RH13  
Manufacturer: Lex  
Model Number: BBLEO-3I525A-RH13

ports COM

Mini PC tres compact sans ventilateurs avec Processeur ATOM, 2 ports LAN et 2

Spécifications du Boitier

|                        |                         |
|------------------------|-------------------------|
| Dimension              | 50 H x 240 W x 124 D mm |
| Material               | Aluminum                |
| Color                  | Black                   |
| VESA Mounting (option) | 75 x 75 mm              |
| Weight                 | 1.22 Kgs ( Incl. M/B )  |
| Storage Space          | 2.5" HDD                |

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| CPU type          | Intel Atom D525 1.8 GHz processor (Dual core processor)                                                     |
| MB Chipset        | Intel Atom D525 + ICH8M (82801 HBM)                                                                         |
| Graphics          | Intel Luna Pier Refresh Pineview-D Integrated Graphics Engine<br>Dynamic Video Memory Technology (DVMT 4.0) |
| Memory            | 1 x DDR3 SO-DIMM socket (max. 4 GB)                                                                         |
| NAND flash memory | CF Card Type II socket for ATA interface                                                                    |
| SATA              | Two SATA ports with independent DMA operation supported                                                     |
| Audio             | Intel High Definition Audio Specification Rev.1.0 Compliant<br>Line-out / Mic-in / Lline-in support         |
| LAN               | 2 x Realtek RLT8111DL 10 / 100 / 1000 Mbps.                                                                 |

&gt;

|                              |                                                                                                  |
|------------------------------|--------------------------------------------------------------------------------------------------|
| IO function                  | 1 x RS232 + 1 x RS422/485<br>Support PS/2 keyboard & mouse                                       |
| USB                          | 2 x external USB 2.0 + 5 x internal USB2.0                                                       |
| DIO & WDT                    | Hardware digital Input & Output, 8xDI / 8xDO<br>Hardware Watch Dog Timer, 0~255 sec programmable |
| Expansion interface          | 1 x Mini PCI socket<br>2 x PCIe mini card for PCIe & USB interface                               |
| Power                        | On board DC +12V±5% convert to +3V/+5V for system                                                |
| Dimensions                   | 145 x 102 mm (3.5 inch) (MB)<br>50H x 240W x 124D mm (Chassis)<br>0~45°C (2.5" HDD / CF Card)    |
| System Operating Temperature | Please upgrade the hard drive to industrial grade for better temperature performance             |
| Operating Humidity           | 5~95%, non-condensing                                                                            |

## Specifications

---

Ce produit a ete rajouté a notre catalogue le mercredi 13 juin 2012