

>



Product Name: HBJC501F9Q-Q87-B  
Manufacturer: Jetway  
Model Number: BBJEHBJC501F9Q-Q87-B

Mini PC Fanless Hautes performance : - 4th Generation Intel® Core i7 / i5 / i3 /

- Pentium Processor < 45W
- Embedded Long-life Series, Planned Lifecycle Through Q1'2018
  - Intel HD 4000/5000 Graphics, DirectX 11.1
  - Supports up to 2 Displays, HDMI, DVI-I
  - Supports iAMT 9.0 Function
  - ECO-design for EuP/ErP

|                           |                                                                                                                |                       |
|---------------------------|----------------------------------------------------------------------------------------------------------------|-----------------------|
| Model No                  | JBC501F9Q-Q87-B                                                                                                | JBC501F9QW-Q87-B      |
| Part No                   | HBJC501F9Q-Q87-B                                                                                               | HBJC501F9QW-Q87-B     |
| Motherboard Specification |                                                                                                                |                       |
| CPU                       | 4th Generation Intel® Core i7 / i5 / i3 / Pentium Processor < 45W<br>Socket LGA 1150 (Formerly Haswell)        |                       |
| Chipset                   | Intel Q87 Chipset                                                                                              |                       |
| Memory                    | 2 x 204-pin SODIMM DDR3-1600 Dual Channel (up to 16 GB)                                                        |                       |
| Graphics                  | Requires Intel Core processor with Intel HD Graphics                                                           |                       |
| LAN                       | 1 x Intel i217LM PHY Gigabit LAN (iAMT 9.0)<br>1 x Intel i211AT PCI-E Gigabit LAN                              |                       |
| Audio                     | Realtek ALC662 HD Audio codec                                                                                  |                       |
| Storage                   | 4 x SATA3 6Gb/s Ports with RAID 0, 1, 5, 10 , JBOD<br>1 x Shared mSATA/mini-PCI Express Combo slot (Full-size) |                       |
| Wireless / Mini-PCIE Slot | 1 * Mini-PCI Express Slot (Half-size)                                                                          | Wireless 802.11 b/g/n |
| USB                       | Embedded 4 * USB 3.0 & 2 * USB 2.0                                                                             |                       |
| MB Form Factor            | Mini-ITX (170mm x 170mm)                                                                                       |                       |
| Chassis Specification     |                                                                                                                |                       |

>

|                    |                                                                                                                              |
|--------------------|------------------------------------------------------------------------------------------------------------------------------|
| Product size       | 260 (W) * 208 (D) * 58.5 (H) mm                                                                                              |
| Color              | Black                                                                                                                        |
| Storage            | 1 * 2.5" SATA Drive Bay                                                                                                      |
|                    | 1 * Power Button                                                                                                             |
| Front I/O Port     | 1 * HDD LED                                                                                                                  |
|                    | 2 * USB 2.0 ports                                                                                                            |
|                    | 6 * DB9 punchouts                                                                                                            |
|                    | 1 * +9 ~ +24V 4-pin MINI DIN jack                                                                                            |
|                    | 1 * HDMI (up to 1920 x 1080)                                                                                                 |
|                    | 1 * DVI-I (up to 1920 x 1080)                                                                                                |
|                    | 1 * RS232/422/485 jumperless COM port                                                                                        |
| Rear I/O Port      | 4 * RS232 COM port                                                                                                           |
|                    | 4 * USB 3.0 ports                                                                                                            |
|                    | 2 * RJ-45 ports                                                                                                              |
|                    | 1 * Line-out jack                                                                                                            |
|                    | 1 * MIC-in jack                                                                                                              |
|                    | 2 * SMA Connector for WiFi Antenna                                                                                           |
|                    | These connectors may not be fully usable with chassis closed, but the information is provided for customer alternative uses. |
| Other Internal     | 1 * 24-bit Dual Channel LVDS connector/inverter (CHRONTEL CH7511B chipset up to                                              |
| Headers            | 1920 x 1200)                                                                                                                 |
|                    | 1 * PCI-E 2.0 x4 Slot                                                                                                        |
|                    | 1 * Chassis Intrusion header                                                                                                 |
|                    | 1 * AT/ATX mode select jumper                                                                                                |
|                    | 1 * 8-bit GPIO Header                                                                                                        |
| Environment        | Operating Temperature : 0 ~ 40°C                                                                                             |
|                    | Storage Temperature : -20 ~ 85°C                                                                                             |
|                    | 19V 120W AC-DC Adapter x1                                                                                                    |
|                    | Power Cord x1                                                                                                                |
|                    | Wall Mount Kit                                                                                                               |
| Standard Accessory | DVI-to-VGA adapter x1                                                                                                        |
|                    | DIN RAIL x2                                                                                                                  |
|                    | DVD Disk x1                                                                                                                  |
|                    | Manual x1                                                                                                                    |
|                    | WIFI antenna (with HBJC501F9QW-Q87-B model)                                                                                  |
| Certificate        | CE,FCC,ErP For Barebone                                                                                                      |
|                    | CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter                                                                                   |

Specifications

>

*Ce produit a ete rajouté a notre catalogue le jeudi 24 septembre 2015*