

>



Product Name: HBJC501F9Q-Q87-B  
 Manufacturer: Jetway  
 Model Number: BBJEHBJC501F9Q-Q87-B

Mini PC Fanless Hautes performance : - 4th Generation Intel® Core i7 / i5 / i3 /

Pentium Processor < 45W

- Embedded Long-life Series, Planned Lifecycle Through Q1'2018
- Intel HD 4000/5000 Graphics, DirectX 11.1
- Supports up to 2 Displays, HDMI, DVI-I
- Supports iAMT 9.0 Function
- ECO-design for EuP/ErP

Model No	JBC501F9Q-Q87-B	JBC501F9QW-Q87-B
Part No	HBJC501F9Q-Q87-B	HBJC501F9QW-Q87-B
Motherboard Specification		
CPU	4th Generation Intel® Core i7 / i5 / i3 / Pentium Processor < 45W Socket LGA 1150 (Formerly Haswell)	
Chipset	Intel Q87 Chipset	
Memory	2 x 204-pin SODIMM DDR3-1600 Dual Channel (up to 16 GB)	
Graphics	Requires Intel Core processor with Intel HD Graphics	
LAN	1 x Intel i217LM PHY Gigabit LAN (iAMT 9.0) 1 x Intel i211AT PCI-E Gigabit LAN	
Audio	Realtek ALC662 HD Audio codec	
Storage	4 x SATA3 6Gb/s Ports with RAID 0, 1, 5, 10 , JBOD 1 x Shared mSATA/mini-PCI Express Combo slot (Full-size)	
Wireless / Mini-PCIE Slot	1 * Mini-PCI Express Slot (Half-size)	Wireless 802.11 b/g/n
USB	Embedded 4 * USB 3.0 & 2 * USB 2.0	
MB Form Factor	Mini-ITX (170mm x 170mm)	
Chassis Specification		

&gt;

Product size	260 (W) * 208 (D) * 58.5 (H) mm	
Color	Black	
Storage	1 * 2.5" SATA Drive Bay	
Front I/O Port	1 * Power Button	
	1 * HDD LED	
	2 * USB 2.0 ports	
	6 * DB9 punchouts	
	1 * +9 ~ +24V 4-pin MINI DIN jack	
	1 * HDMI (up to 1920 x 1080)	
Rear I/O Port	1 * DVI-I (up to 1920 x 1080)	
	1 * RS232/422/485 jumperless COM port	
	4 * RS232 COM port	
	4 * USB 3.0 ports	
	2 * RJ-45 ports	
	1 * Line-out jack	
	1 * MIC-in jack	
	2 * SMA Connector for WiFi Antenna	
	These connectors may not be fully usable with chassis closed, but the information is provided for customer alternative uses.	
	Other Internal Headers	1 * 24-bit Dual Channel LVDS connector/inverter (CHRONTEL CH7511B chipset up to 1920 x 1200)
Environment	1 * PCI-E 2.0 x4 Slot	
	1 * Chassis Intrusion header	
	1 * AT/ATX mode select jumper	
	1 * 8-bit GPIO Header	
	Operating Temperature : 0 ~ 40°C	
Standard Accessory	Storage Temperature : -20 ~ 85°C	
	19V 120W AC-DC Adapter x1	
	Power Cord x1	
	Wall Mount Kit	
	DVI-to-VGA adapter x1	
	DIN RAIL x2	
	DVD Disk x1	
Manual x1		
Certificate	WIFI antenna (with HBJC501F9QW-Q87-B model)	
	CE,FCC,ErP For Barebone	
	CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter	

## Specifications

---

>

*Availability: This product was added to our catalog on Thursday 24 September, 2015*