

Product Name: SP8000G
Manufacturer: VIA
Model Number: CMVISP8000EG

Processor	- VIA Eden™ 800Mhz Fanless
Chipset	- VIA CN400 North Bridge - VIA VT8237 South Bridge
System Memory	- 1 DDR266/333/400 DIMM socket - Up to 1GB memory size
VGA	- Integrated VIA UniChrome™Pro AGP graphics with MPEG-2 decoder /MPEG-4 Accelerator
Expansion Slots	- 1 PCI
Onboard IDE	- 2 X UltraDMA 133/100 Connector
Onboard Serial ATA	- 2 SATA Connectors
Onboard LAN	- VIA VT6103 10/100 Base-T Ethernet PHY
Onboard Audio	- VIA VT1617A 6channel AC' 97 codec
Onboard TV Out	- VIA VT1623 TV Encoder
Onboard 1394	- VIA VT6307S IEEE 1394 Firewire
Back Panel I/O	- 1 PS2 mouse port - 1 PS2 keyboard port - 1 RJ-45 LAN port - 1 Serial port - 2 USB 2.0 ports - 1 VGA port - 1 PCA port (SPDIF or TV out) - 1 S-video port - 3 Audio jacks: line-out, line-in and mic-in (Smart 5.1 Support)

Onboard I/O Connectors	- 3 USB connector for 6additional USB 2.0 ports - 1 1394 connector for 1 1394 port - 1 Serial port connector for a second com port - 1 VIP connector - 1 Front-panel audio connector (Mic-in and Line-out) - 1 CD audio-in connector - 1 FIR connector - 1 CIR connector (Switchable for KB/MS) - 1 LPT port connector - 1 Wake-on-LAN connector - 2 Fan connectors: CPU/Sys FAN - 1 I2C connector - 1 LVDS/TTL module connector (Optional) - 1 +12V power connector - ATX power connector
BIOS	- Award BIOS - 4/8Mbit flash memory
System Monitoring & Management	- CPU voltage monitoring - Wake-on-LAN, Keyboard Power-on, Timer Power-on - System power management - AC power failure recovery
Operating Temperature	0~50°C
Operating Humidity	0% ~ 93% (relative humidity; non-condensing)
Form Factor	- Mini-ITX (6 layer) - 17 cm x 17 cm

Ce produit a ete rajouté a notre catalogue le mercredi 08 juin 2005