

>

>



Product Name: LV674
Manufacturer: Commell
Model Number: CMCOLV-674

Intel Pentium D / Celeron D LGA775 processor (170 x 170mm)

533/800/1066MHz FSB , EM64T supported
Intel 945G & ICH7R .2 x DDR2 533/667MHz SDRAM up to 2GB.
Intel GMA950 technology . 4 x SATA II with 300MB/s transfer rate.
Realtek 7.1-CH High Definition Audio. Onboard GPIO port.
1 x Mini-PCI socket and 1 x PCI-Express slot.
4 x Giga LAN , 2 x IEEE 1394 , 4 x USB 2.0 , S/PDIF.
2 x RS232 , GPIO , IrDA.

Spécifications

Form Factor	Mini-ITXexpress Motherboard (170 x 170 mm)
CPU	Intel Pentium D / Celeron D LGA775 533/800/1066 FSB. Support EM64T , Dual Core
Memory	2 x DDR2 533/667 MHz SDRAM up to 2GB
Chipset	Intel 945G & ICH7R
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset internal timer for 1min ~ 255
Power Management	ACPI 1.0 compliant, supports power saving mode ATX
PCI Enhanced IDE	PS/2 Ultra ATA/100 IDE channel up to 2 ATAPI devices
VGA Interface	Intel 945G integrated GMA(Graphic Media Accelerator) 950 Technology
Video Memory	Up to 224MB shared with system memory
Serial ATA Interface	4 x Serial ATA II Interface with 300MB/s transfer rate.Support RAID 0,1,5,10 function

>

Audio Interface	Intel ICH7R integrated with Realtek ALC882 7.1 CH High Definition Audio
LAN Interface	4 x Marvell E8053 Gigabit Ethernet Controller
Solid State Disk	IDE1 supports DiskOnModule +5V power supply
GPIO Interface	Onboard programmable 8-bit digital I/O interface
Extend Interface	1 x Onboard 16x PCI-Express slot (x 1 mode compatible) 1 x Min-PCI socket
External I/O Port	4 x RJ45 LAN port, 1x DB15 VGA port, 1x PS/2 Keyboard / Mouse ports 2 x RS232 Serial port , 1 x IEEE1394 port, 2x USB, 2x FireWire
External Audio Port	Line In, 2x Line Out, Front, Rear , Center/Subwoofer and side outputs.
Internal I/O Port	1 x silm FDD, 1 x IrDA , 2 x USB 2.0 , 1 x IEEE 1394 , 1 x CDIN , 1 x S/PDIF
Power Requirement	Standard 24-pin ATX power supply. (20-pin is compatible)
Board Dimension	170mm x 170 mm (L x W)
Operation Temperature	0 ~ 60oC (32 ~ 140oF)

Ce produit a ete rajouté a notre catalogue le samedi 03 décembre 2005