



Product Name: LE-364C10

Manufacturer: Commell

Model Number: CMCOLE-364C10

3.5" Fanless Miniboard with VIA Eden CPU.

Embedded VIA 800MHz CPU with 133 MHz FSB.

VIA CN400 & VT8237 Chipset

184-pin DDR266/333/400 SDRAM up to 1GB

MPEGII/MPEG-4 hardware accelerator integrated

18/24-bit LVDS interface

Mini-PCI and CompactFlash socket interface

One 10/100Mbps LAN , 2 x USB 2.0 , 2 x COM

Specifications

- Form Factor: 3.5" Fanless Embedded miniboard
- CPU: Embedded VIA Eden 800MHz CPU
- Memory: Onboard 1 x 184-pin DDR266/333/400 SDRAM up to 1 GB
- Chipset : VIA CN400 & VT8237
- Real Time Clock : Chipset Integrated RTC with onboard lithium battery
- Watchdog Timer : Winbond W83697HF with system generates 256 levels reset.
- Power Management : ACPI 1.0 compliant, supports power saving mode with ATX PSU
- PCI Enhanced IDE: One ATA133 IDE channel supports up to 2 ATAPI devices. Onboard 1 x 44-pin IDE connectors
- VGA Interface: VIA CN400 integrates S3 Graphics UniChrome Pro IGP graphic core. MPEGII/MPEG-4 hardware accelerator integrates and 64 MB of video memory shared with system.
- LCD Interface: 18/24-bit LVDS interface.
- LAN Interface: 1 x VIA VT6103 10/100Mbps PHY.
- Audio Interface: Realtek ALC201A AC97 Codec.
- Solid State Disk: IDE1 supports DiskOnModule with + 5V power supply. 1 x CF socket.
- Internal I/O Ports: 1x IrDA port, 1x Parallel and 2 x USB ports. 1 x Serial Port, 1x slim FDD , 1 x CDIN, 1 x 10-pin audio port. 2 x fan connectors. 1 x 4-pin 12V power input. 1 x 4-pin 5V/12V power output.
- External I/O Ports: 1 x RJ45 LAN ports, 1x DB15 VGA port and 1x PS/2 port, 1x RS232 port, 1 x Phone jack. 1x DC Jack

>

- Extended Interface: 1 x Mini-PCI slot. Extended PCI interface through optional riser card up to 2 devices.
- Power Requirement : DC 12V input
- Board Dimension : 146 mm x 101 mm (L xW)

LE-364C10 Same as LE-364 but change processor to C3 1GHz

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011