

>



Product Name: Carte mere Commell LS-572D2
Manufacturer: Commell
Model Number: CMCOLS-572D2

Intel® Core™ 2 Quad / Core™ 2 Duo Desktop , 800/1066/1333 MHz FSB

Intel® Q35 & ICH9DO , DDRII 667/800 MHz up to 4.0 GB
Onboard VGA , Dual DVI or LVDS interface
1 x PCI slot & 1 x Mini-PCI socket
Onboard 2 x Intel® Gigabit LAN , HD Audio , LPT , SMBUS
1 x RS-232/422/485 & 5 x RS232 , 8 x USB 2.0 , IrDA , GPIO

Form Factor

Processor

Memory

Chipset

Real Time Clock

Watchdog Timer

Power Management

VGA Interface

DVI or LVDS Interface

Video Memory

Serial ATA Interface

Audio Interface

LAN Interface

GPIO Interface

Extend Interface

5.25" SBC (203 x 146 mm)
Intel® Core™ 2 Quad / Core™ 2 Duo Desktop LGA775
800/1066/1333 MHz FSB.
2 x DDR2 667/800 MHz support up to 4.0 GB
Intel® Q35 Express Chipset & ICH9DO
Chipset integrated RTC with onboard lithium battery
Generates a system reset internal timer for 1Min/Sec ~
255 Min/Sec
ACPI 1.0 compliant, supports power saving mode ATX
PSU
Intel® Q35 integrated GMA 3100 Technology
Dual DVI or single LVDS interface
Up to 384MB shared with system memory
4 x Serial ATA II Interface with 300MB/s transfer rate
Support RAID 0,1,5,10 function
Intel® ICH9DO integrated with Realtek ALC888 HD
Audio
2 x Intel® 82573L Gigabit Ethernet Controller
Onboard programmable 8-bit digital I/O interface
1 x PCI slot & 1 x Min-PCI socket

>

I/O Port

2 x RJ45 LAN ports , 1x DB15 VGA port , 1x PS/2
Keyboard / Mouse ports , 1 x RS232/422/485 & 5 x
RS232 Serial ports , 8 x USB 2.0 ports , 1 x IrDA , HD
Audio ports , 1 x SMBUSDVI or LVDS interface , 1 x
LPT , 1 x slim FDD , 1 x GPIO

Power Requirement

Standard 24-pin ATX power supply and P4 4-pin 12V .
(20-pin is compatible)

Board Dimension

203mm x 146 mm (L x W)

Operation Temperature

0 ~ 60°C (32 ~ 140°F)

LS-572D2

Onboard VGA , 2 x Intel Giga LAN , 8 x USB 2.0 ,
PCI & Mini-PCI , FDD,HD Audio , 4 x SATA , 6 x
COM , 2 x DVI

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011