

>



Product Name: Carte mere Commell LS-572D

Manufacturer: Commell

Model Number: CMCOLS-572D

Intel® Core™ 2 Quad / Core™ 2 Duo Desktop , 800/1066/1333 MHz FSB

Intel® Q35 & ICH9DO , DDRII 667/800 MHz up to 4.0 GB

Onboard VGA , Dual DVI or LVDS interface

1 x PCI slot & 1 x Mini-PCI socket

Onboard 2 x Intel® Gigabit LAN , HD Audio , LPT , SMBUS

1 x RS-232/422/485 & 5 x RS232 , 8 x USB 2.0 , IrDA , GPIO

Form Factor

Processor

5.25" SBC (203 x 146 mm)

Intel® Core™ 2 Quad / Core™ 2 Duo Desktop LGA775
800/1066/1333 MHz FSB.

Memory

2 x DDR2 667/800 MHz support up to 4.0 GB

Chipset

Intel® Q35 Express Chipset & ICH9DO

Real Time Clock

Chipset integrated RTC with onboard lithium battery

Watchdog Timer

Generates a system reset internal timer for 1Min/Sec ~
255 Min/Sec

Power Management

ACPI 1.0 compliant, supports power saving mode ATX
PSU

VGA Interface

Intel® Q35 integrated GMA 3100 Technology

DVI or LVDS Interface

Dual DVI or single LVDS interface

Video Memory

Up to 384MB shared with system memory

Serial ATA Interface

4 x Serial ATA II Interface with 300MB/s transfer rate
Support RAID 0,1,5,10 function

Audio Interface

Intel® ICH9DO integrated with Realtek ALC888 HD
Audio

LAN Interface

2 x Intel® 82573L Gigabit Ethernet Controller

GPIO Interface

Onboard programmable 8-bit digital I/O interface

Extend Interface

1 x PCI slot & 1 x Min-PCI socket

>

I/O Port

2 x RJ45 LAN ports , 1x DB15 VGA port , 1x PS/2
Keyboard / Mouse ports , 1 x RS232/422/485 & 5 x
RS232 Serial ports , 8 x USB 2.0 ports , 1 x IrDA , HD
Audio ports , 1 x SMBUSDVI or LVDS interface , 1 x
LPT , 1 x slim FDD , 1 x GPIO

Power Requirement

Standard 24-pin ATX power supply and P4 4-pin 12V .
(20-pin is compatible)

Board Dimension

203mm x 146 mm (L x W)

Operation Temperature

0 ~ 60°C (32 ~ 140°F)

LS-572D

Onboard VGA, 2 x Intel Giga LAN, 8 x USB 2.0, PCI &
Mini-PCI, FDD,HD Audio, 4 x SATA, 6 x COM, 1 x
DVI

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011