

>



Product Name: Carte mere Commell FS-97CEDG2
Manufacturer: Commell
Model Number: CMCOFS-97CEDG2

Intel® Core™ 2 Duo / Core™ Duo processor , 533 / 667 MHz FSB

Intel® 945GME and ICH7M chipset
DDRII 533 / 667 MHz up to 3.0 GB , Onboard VGA , HDTV
18-bit Dual Channel LVDS & DVI interface
Onboard 2 x Intel® Gigabit LAN , 5.1 channel Audio
RS232/422/485 , USB 2.0 , 8-bit GPIO , LPT , FDD , IrDA
2 x Mini-PCI & CompactFlash socket

Form Factor	PICMG 1.0 CPU Card
CPU	Intel Core™ Duo / Core 2 Duo Merom with Socket M @ 533 / 677 MHz FSB. 2 x DDR2 533/667 MHz SDRAM up to 3.0 GB
Chipset	Intel 945GME & ICH7M
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset internal timer for 1min ~ 255 min
Power Management	ACPI 1.0 compliant, supports power saving mode
PCI Enhanced IDE	1 x Ultra ATA/100 IDE channel up to 2 ATAPI devices
VGA Interface	Intel 945GM integrated GMA (Graphic Media Accelerator) 950 Technology
Video Memory	Up to 224MB shared with system memory
Serial ATA Interface	2 x Serial ATA Interface with 150 MB/s transfer rate.
Audio Interface	Realtek ALC655 5.1 channel Audio
LAN Interface	2 x Intel 82573L Gigabit Ethernet .(FS-97CDG2 Model only)

>

Solid State Disk	IDE supports 40-pin DiskOnModule .CompactFlash Type-II on the rear .
GPIO Interface	Onboard programmable 8-bit digital I/O interface
Extend Interface	2 x Min-PCI socket
External I/O Port	2x RJ45 LAN port, 1x DB15 VGA port, 1 x PS/2 Keyboard / Mouse ports, 1 x RS232 & 1 x RS232/422/485, 1 x FDD, 1 x IrDA , 1 x LPT 4 x USB 2.0,
Internal I/O Port	1 x 8-bit GPIO, 1 x Audio, 1 x CDIN , 1x DVI LVDS and LCD inverter connector , HDTV
Power Requirement	+5V , +12V input & 5VSB Requirement
Board Dimension	338mm x 122 mm (L x W)
Operation Temperature	0 ~ 60 •Ž
FS-97CEDG2	Same as above and with secondary Gigabit LAN

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011