

>



Product Name: Carte mere Commell FS-A70G2
Manufacturer: Commell
Model Number: CMCOFS-A70G2

Intel® Core™ 2 Duo / Core™ 2 Quad processor, 533/800/1066MHz FSB

Intel® Q965 & ICH8DO chipset, DDRII 533/667/800MHz up to 4GB,
Onboard VGA, Onboard 2 x Intel® Gigabit LAN, 6 x SATA with RAID 0/1/5/10
RS232/422/485, USB 2.0, 8-bit GPIO, LPT, FDD, IrDA, Mini-PCI

Form Factor	PICMG 1.3 CPU Card
CPU	Intel Core™ 2 Duo / Pentium D / Pentium 4 processor LGA775 @ 533 / 800 / 1066 MHz FSB
Memory	2 x DDR2 533/667/800 MHz SDRAM up to 4.0 GB
Chipset	Intel Q965 & ICH8DO
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset internal timer for 1min ~ 255 min
Power Management	ACPI 1.0 compliant, supports power saving mode
VGA Interface	Intel Q965 integrated GMA (Graphic Media Accelerator) 3000 Technology
Video Memory	Up to 256MB shared with system memory
Serial ATA Interface	6 x Serial ATA Interface with 300 MB/s transfer rate. support RAID 0/1/5/10 and Intel Matrix Storage Technology
Audio Interface	Realtek ALC260 2-channel Audio
LAN Interface	2 x Intel 82573L Gigabit Ethernet .(FS-A70G2 Model only)
GPIO Interface	Onboard programmable 8-bit digital I/O interface
Extend Interface	1 x Mini-PCI socket
External I/O Port	2x RJ45 LAN port (FS-A70G2 model) , 1x DB15 VGA port, 1 x PS/2 Keyboard / Mouse ports, 1 x RS232 & 1 x RS232/422/485, 1 x FDD, 1 x IrDA , 1 x LPT 6 x USB 2.0, 1 x 8-bit GPIO, 1 x Audio, 1 x CDIN
Internal I/O Port	,

>

Expansion Interface

PICMG 1.3 Interface support 1 x PCI-Express and 1 x 4 or 4 x 1 PCI-Express , 4 PCI bus master, and 4 USB2.0 Interface

Power Requirement

+5V , +12V input & 5VSB Requirement

Board Dimension

338mm x 126 mm (L x W)

Operation Temperature

0 ~ 60 °C

FS-A70G2

Intel Core™ 2 Duo PICMG 1.3 with onboard VGA, SATA, USB 2.0, Audio, RS232/422/485, Mini-PCI, 2 x Giga LAN

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011