

>



Product Name: Carte mere Commell FS-A71G2
Manufacturer: Commell
Model Number: CMCOFS-A71G2

Intel® Core™ 2 Duo (Merom)processor @ 800 MHz FSB

Intel® GME965 & ICH8M , DDRII 533 / 667 MHz up to 3GB , Onboard VGA
24-bit Dual Channel LVDS , 2 x Mini-PCI sockets, HDTV
Onboard 2 x Intel® Gigabit LAN , HD Audio , CF socket
RS232/422/485 , 6 x USB 2.0 , 8-bit GPIO , LPT , FDD , IrDA ,

Form Factor	PICMG 1.3 SBC (338 x 126 mm)	
CPU	Intel® Core™ 2 Duo processor Merom with Socket P @ 800 MHz FSB.	2 x DDR2 533/667 MHz DIMM up to 3.0 GB
Chipset	Intel® GME965 & ICH8M	
Real Time Clock	Chipset integrated RTC with onboard lithium battery	
Watchdog Timer	Generates a system reset internal timer for 1sec/min ~ 255 sec/min	
Power Management	ACPI 1.0 compliant, supports power saving mode	
VGA Interface	Intel® GME965 integrated GMA (Graphic Media Accelerator) X3100 Technology	
Video Memory	Up to 384 MB shared with system memory	
Serial ATA Interface	3 x Serial ATA II Interface with 300 MB/s transfer rate.	
Audio Interface	Realtek ALC888 HD Audio	
LAN Interface	2 x Intel® 82573L Gigabit Ethernet	
Solid State Disk	IDE support 40-pin DiskOnModule,1 x CompactFlash Type-II	
GPIO Interface	Onboard programmable 8-bit digital I/O interface	
Extend Interface	2 x Min-PCI sockets	

>

External I/O Port	RJ45 LAN port, 1 x DB15 VGA port, 1 x PS/2 Keyboard / Mouse ports
Internal I/O Port	1 xRS232 & 1 x RS232/422/485, 1 x FDD, 1 x IrDA, 1 x LPT 1 x Audio, 6 x USB 2.0, 1 x 8-bit GPIO, 1 x CDIN, LVDS and LCD inverter connector , HDTV
Power Requirement	+5V, +12V & 5VSB
Board Dimension	338mm x 126 mm (L x W)
Operation Temperature	0 ~ 60°C (32 ~ 140°F)
FS-A71G2	PICMG 1.3 SBC support Intel® Core™ 2 Duo with onboard VGA, SATA, USB 2.0 ports Audio, RS232/422/485, Min-PCI, 2 x Giga LAN

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 15 avril 2011