

>



Product Name: MP57-DU (W/O ODD)

Manufacturer: Aopen

Model Number: BBAOMP57-DU

Mini PC Aopen hautes performances

- Intel® Calpella QM57(MP57) /HM55(MP55) platform, supports Intel Arrandale Core i3/ i5/ i7
- Intel® Core™ Processors with Intel Graphics Media Accelerator HD deliver enthusiast class media capabilities
- High speed dual channels DDRIII memory up to 1066MHz and max 8G
- Supports dual screen mode to extend your viewing area or display multiple windows for speeding up works
- Adapt EPA5.0 ready to reduce energy costs by using an average of 50% less power than traditional PCs (MP57 only)
- Excellent performance with full 1080P high definition video playback ability
- High transmitting speed e-SATA port for external storage
- Quiet small system zidle model 22db only

Model	MP57-DU
Dimension:	6.65(W)x1.97(H)x6.65(D)inch 169(W)x50(H)x169(D)mm
Volume:	1.4L

>

Weight (Kg/Pound):	1.7KG/3.75 pound(N.W.)
Color:	Black/Gray
Supported CPU:	Socket : Intel Mobile CPU Socket G1 Type : Intel Mobile Core i3/i5/i7 (f 35W)
vPro Support:	Yes
TPM:	Infineon SLB 9635 TT 1.2 TPM
Chipset:	Intel QM57 Chipset Dual Channel Mode : Dual Channel
Supported Memory:	Memory Type : SO-DIMM DDRIII x 2 DDR : DDRIII 1066 Max memory size : 8GB
Graphics:	DVI-i Port x 1 HDMI Port x 1
Expansion Slot:	Full Size mini Card x 1 Half Size Mini Card x 1
Audio:	Type : Realtek ALC662 HD Audio CODEC on-Board Channel : 5.1 Channel
LAN:	Intel 82577LM 10/100/1000 Mbps LAN Controller
USB:	Chip : Integrated in chipset USB 2.0 : USB 2.0 port x 6 (Rear x 4 / Front x 2)
Thermal Solution:	AOpen Silentek 5.0
Form Factor:	Mini-ATX
Storage Bay:	S-ATA Slot-in Slim Optical Drive Bay x 1 2.5" SATA HDD Bay x 1
Front Panel I/O:	Power touch Button x 1 USB 2.0 port x 2 HDMI Port x 1 DC 20V Jack x 1 DVI-i Port x 1 USB 2.0 Port x 4
Rear Panel I/O:	eSATA Port x 1 RJ-45 LAN Jack x 1 Line-In (Surround-Out L/R)* with S/PDIF_Out x 1 Line_Out (Front-Out L/R)* x 1 Mic-In(Central/Subwoofer out) * x 1 Security Hole x 1
Power Supply:	90W (20V, 4.5A) AC Power Adapter
Input Voltage:	AC 100~240V
Environment:	Operating Temperature : 10 ~ 35°C(50 ~ 95°F) Storag Temperature : -10 ~ 48°C (14 ~ 118.4°F) Operating Humidity : 5 ~ 90%RH

>

Slim Type Optical Drive: N/A
20V 90W Power Adapter x 1
Power Cord x 1
DVI to VGA Adapter x 1
Accessory: S/PDIF Converter x 1
Riser card x 1
Driver CD x 1
Easy Installation Guide x 1
Supported OS: Windows 7, Vista Ultimate / Home Premium / Home Basic

Specifications

Ce produit a ete rajouté a notre catalogue le mardi 19 avril 2011