

>



Product Name: EITX-3001-1N13A1
Manufacturer: VIA
Model Number: CMVIEITX-3001-1N13A1

- Em-ITX form factor: 17cm (W) x 12 cm (L)
- Low profile design
- Dual-sided I/O coastlines
- Integrated VIA Chrome9 HCM with DX9 3D/2D graphics
- Hardware acceleration for MPEG-2, WMV9, VC1, and H.264 codecs
- Versatile display configuration inc. VGA, HDMI and LVDS multi-display
- Gigabit Networking
- COM ports inc. dual RS-232 and dual RS-232/422/485
- Five USB 2.0 host ports and one USB device port
- Supports 5-wire/4-wire resistive touch interface connector
- Fanless and ultra low power consumption

| | | |
|------------------|-------------------------|--|
| Processor System | Processor | 1.3GHz VIA Nano™ E |
| | Front Side Bus Speed | 800 MHz |
| | L2 Cache | 1 MB |
| | Chipset | VIA VX855 Unified Digital Media IGP chipset |
| | BIOS | AMI BIOS, 8MBit SPI Flash BIOS |
| | System Power Management | Timers Power On ACPI supported |
| Memory | Technology | 1 x DDR2 800/667/533 MHz 200-pin SDRAM SODIMM socket |
| | Max. Capacity | Up to 2GB memory size |

| | | |
|----------|--------------------------|---|
| > | | |
| | | |
| Graphic | Controller | Integrated VIA Chrome 9™ HCM DX9 3D/2D graphics & video processor, built-in Unified Video Decoding Accelerator, supports MPEG-2, WMV9/VC1, and H.264 video decoding acceleration |
| | Display Memory | Optimized Unified Memory Architecture (UMA), Supports up to 512 MB frame buffer using system memory |
| | CRT Interface | Onboard 1 x VGA connector as JVGA1Supports CRT resolution up to 1920 x 1440 |
| | LVDS Interface | Supports 1 x 24-bit single-channel LVDS interface with inverter control signals by an onboard 2x15-pin wafer box connector as LVDS1Panel resolution support up to WXGA (1366 x 768)Onboard 5V/3.3V LCD power switch (default at 3.3V) |
| | HDMI Interface | AD 9389B HDMI transmitterOnboard 1 x dual-link HDMI connector with flange as JHDMI |
| | Dual Independent Display | Supports CRT + LVDS , CRT + HDMI and LVDS + HDMI at same resolutions, same pixel depths, and same refresh rates |
| Ethernet | Controller Interface | VIA VT6122 Gigabit Ethernet controller Supports 1 x RJ-45 connectorSupports Wake On LAN (WOL)Supports Preboot Execution Environment (PXE) |
| HD Audio | Controller | VIA VT1708B High Definition Audio CodecOnboard TI TPA1517 6-W stereo Audio power amplifier |
| | Interface | Supports Line-in, Speaker-out, Mic-in connectors by 3*3.5Ø audio jacks |

>

| | | |
|-------------------|--------------------|--|
| Serial | USB Host port | Supports 6 x USB 2.0 host ports in: 4 x USB 2.0 host ports by 2 pairs of double mini-DIN connector as ••USB1~USB4 Reserved 1 x USB 2.0 port by a 1 x 6-pin header with support of ••individual VCC power for connection with VIA EMIO-1530 Wireless LAN as JWLAN1 |
| | USB Device Port | Supports 1 x USB device port by a mini-DIN connector Fintek F81865 LPC I/O controller |
| | Serial Ports | Supports 4 x COM ports in: 2 x RS-232/422/485 by two DB-9 connectors as COM 1 and COM ••2, configurable via BIOS setup. Supports RS-485 AutoFlow control functions of COM1 and COM2 2 x RS-232 by two 2x5-pin headers as COM 3 and COM 4•• |
| Resistive Touch | Controller | EETI ETP-CP-S5XU resistive touch panel controller |
| | Interface | 1 x 5-wire/4-wire resistive touch sensor interface by a 1 x 5pin header as TOUCH _R1 |
| DIO | Digital I/O | 1 x 2 x6-pin header. Supports 8-bit GPIO, with 5VDC and 12VDC power source |
| PS2 | Keyboard & Mouse | 1 x 2x5-pin header. Supports PS2 keyboard/mouse interface |
| Storage interface | Serial ATA | JMicron JMH330 SATA controller1 x SATA II port, maximum data transfer rate up to 300MB/sOnboard power connector output 5V support 2.5" SATA hard disk drive |
| | Compact Flash | 1 x Onboard socket. Supports type I/II CompactFlash disk |
| H/W Monitoring | Temperature Sensor | Built-in one Thermal Sensor by onboard 1x3-pin headers |
| System Indicator | Power Status LED | 1 x Green color LED |
| | HDD Activity LED | 1 x Red color LED |

| | | |
|-------------------------------|-------------------------|--|
| > | | |
| | | |
| Watchdog Timer | Output Interval | System reset Programmable 1~255 sec |
| | Front I/O Coastline | 1 x HDD & PWR LED2 x RS-232 / 422 / 485 as COM 1 and COM21 x USB device port by a mini-DIN connector1 x 2-pole of Phoenix power input connector1 x ATX power on/off switch |
| | Onboard I/O Connectors | 1 x VGA connector 1 x Dual-Link HDMI connector with flange as JHDMI4 x USB 2.0 host port by 2 pairs of double mini-DIN connector as USB1~USB41 x RJ45 connector for Gigabit Ethernet connection as J13 x 3.5Ø audio jacks as Mic-in Line-in, and Speaker-out |
| | Rear I/O Coastline | 2 of 2 x 5-pin headers for 2 x RS-232 as COM 3 and COM 42 of 1 x 3-pin headers for 5V/12V selection of COM3 and COM41 of SATA data connector1 of SATA power connector support of 5V for 2.5" HDD1 of 2 x 6-pin header support 8-bit GPIO, with 5VDC and 12VDC power source1 of 1 x 3-pin header for thermal sensor as SEN11 of 1 x 6-pin header for connection with VIA EMIO-1530 wireless LAN card1 of 2 x 15-pin header for signal channel LVDS interface as LVDS1 1 of 1 x 3-pin header for LCD Power 3.3v/5V selection1 of 2 x 5-pin header support PS2 keyboard/mouse interface1 of 1 x 3-pin header for selecting the AT or ATX mode |
| Onboard I/O Pin-headers | Onboard I/O Pin-headers | Built-in onboard DC-to-DC converterAccepts wide range of Power Input of DC 7V ~ 36VSupports AT and ATX mode |
| | Input Voltage | |
| | Power Input Connector | 1 x 2-pole Phoenix connector |
| | AT/ATX Selector | Onboard AT/ATX switch by a 3-pin headers |
| Onboard DC to DC Power Supply | Fuse Rating | 7 A / 125 V |

>

| | | |
|-----------------------------|-----------------------|--|
| Heatsink | Construction | Aluminum modeling |
| | Dimensions (WxHxD) | 230.45 mm x 34 mm x 124.8 mm |
| | Form Factor | Em-ITX |
| Physical Characteristics | Board Dimension | 17 cm (W) x 12 cm (L) |
| | Weight | 1 Kg (net weight of board plus heatsink only) |
| | Operating Temperature | -10°C ~ 60 °C |
| Environmental Specification | Storage Temperature | -20°C ~ 70 °C |
| | Operating Humidity | 10% ~ 90%, relative humidity, non-condensing |
| Software Compatibility | Operation System | Microsoft Windows XP, Windows 7, Microsoft Windows XP Embedded |

Specifications

Ce produit a ete rajouté a notre catalogue le vendredi 20 janvier 2012