

>



Product Name: FSP100-50LG + plates
Manufacturer: Fortron
Model Number: ALIMFLEX100W

Alimentation industrielle 100watts au format FLEX ATX

- Low Ripple & Noise
- Output over voltage protection
- Short circuit protection on all outputs
- Resettable power shut down
- 100% burn-in under high ambient temperature(50)
- Vacuum-impregnated transformer
- MTBF:100K hours at 25
- 100% Hi-pot tested
- Line input fuse protection

INPUT SPECIFICATIONS

ÙInput voltage: 90 - 264 V
ÙInput frequency: 47Hz TO 63 Hz
ÙInput current: 3.0Amps maximum/115 Vrms,60 Hz;
1.5 Amps maximum/230 Vrms,50 Hz;

OUTPUT SPECIFICATIONS

ÙOver voltage protection: +5V output: 5.7V min, 6.5V max;
+3.3V output: 3.7V min, 4.5V max;
+12V output 13.4V min, 15.6V max;
ÙOverload protection: See specification for the detail

GENERAL SPECIFICATIONS

>

ÛHold-up time:	115V/60Hz 17mSec. Minimum@Full Load 230V/50Hz 17mSec. Minimum@Full Load
ÛEfficiency:	>80%
ÛMTBF:	100,000 hours atFull load at 25
ÛPower good signal:	100ms to 500 ms

ENVIRONMENTAL SPECIFICATIONS

ÛOperating temperature:	0 to +50
ÛStorage temperature:	-20 to +80
ÛRelative humidity:	5% to 95% RH non-condensing

OUTPUT SPECIFICATIONS

ÛOver voltage protection:	+5V output: 5.7V min, 6.5V max; +3.3V output: 3.7V min, 4.5V max; +12V output 13.4V min, 15.6V max;
ÛOverload protection:	See specification for the detail

GENERAL SPECIFICATIONS

ÛHold-up time:	115V/60Hz 17mSec. Minimum@Full Load 230V/50Hz 17mSec. Minimum@Full Load
ÛEfficiency:	>80%
ÛMTBF:	100,000 hours atFull load at 25
ÛPower good signal:	100ms to 500 ms

ENVIRONMENTAL SPECIFICATIONS

ÛOperating temperature:	0 to +50
ÛStorage temperature:	-20 to +80
ÛRelative humidity:	5% to 95% RH non-condensing

Specifications

Ce produit a ete rajout   a notre catalogue le samedi 18 f  vrier 2012