

>



Product Name: JNC9KDL-2700

Manufacturer: Jetway

Model Number: CMJEJNC9KDL-2700

Carte Mini-itx dual GigaLan avec Atom D2700

- Next-Generation Intel Cedar Trail-D Platform
- Intel Atom D2700 Processor, 2.13GHz, Dual-Core, 32nm, 10W
- Intel NM10 Express Chipset
- Integrated PowerVR SGX 545 Graphics, 640MHz
- Supports 1080P HD Playback, Blu-ray 2.0, DirectX 9
- Supports Dual Independent Displays
- Supports 2 * DDR3-800/1066 SO-DIMM up to 4GB
- Supports 2 * SATA2 3Gb/s Devices, HD Audio
- Dual Gigabit LAN with Enhanced Surge Protection
- HDMI/VGA and 24-bit LVDS Video Outputs
- Watchdog Timer System Reset, 1-255 min/sec
- Mini-ITX Form Factor (170mm x 170mm)

CPU	Intel Atom D2700 Processor, 2.13GHz, Dual-Core, 32nm, 10W Hyper-Threading Support
Chipset	Intel NM10 Express Chipset
Video	Integrated PowerVR SGX 545 Graphics, 640MHz
Memory	2 * 204-pin DDR3-800/1066 Single Channel SO-DIMM up to 4GB
Expansion Slots	1 * PCI Slot
Storage	2 * SATA2 3Gb/s Connectors
Audio	VIA VT1705 5.1 Channel HD Audio

>

Network	2 * Realtek RTL8111EVL PCI-E Gigabit LAN with Enhanced Surge Protection
LVDS	1 * 24-bit Single Channel LVDS & Inverter Headers
USB	8 * USB 2.0 Ports Total
Other Features	Support ACPI S3, CPU Smart FAN, Watchdog Timer 1-255 min/sec
	4 * USB 2.0 Ports
	1 * PS/2 Mouse Port
	1 * PS/2 Keyboard Port
Rear Panel I/O	2 * RJ-45 Ports
	3 * Audio Ports (Line-in, MIC, Line-out)
	1 * VGA Port
	1 * HDMI Port
	2 * USB Headers for 4 * USB 2.0 Ports
	2 * Fan Headers
	1 * 24-pin ATX Power Connector
Internal I/O	1 * LVDS & Inverter Headers
	1 * Audio Header
	1 * Serial Header (RS232)
	1 * Parallel Header
	Front Panel Headers
BIOS	AMI 16MB DIP Flash ROM
Compliance	CE, FCC, RoHS, ErP
Temperature	Operating Temp 0~40° C
	Storage Temp -20-85° C
Form Factor	Mini-ITX Form Factor (170mm x 170mm)

Specifications

Ce produit a ete rajouté a notre catalogue le lundi 14 mai 2012