

# Industrial Single Board Computer

## Mini-ITX motherboard

### LV-679

Support Intel Core 2 Duo Mobile CPU with DDRII SO-DIMM, CRT, LVDS, DVI, Gigabit LAN, PCI slot, 1394, Mini PCI, 7.1 Channel HD Audio, RS232/422/485 port, Serial ATAll, IDE and Compact Flash socket



|                             |  |
|-----------------------------|--|
| <b>Form Factor</b>          | Mini-ITX motherboard   |
| <b>CPU</b>                  | Support Intel Core 2 Duo Mobile Processor<br>Package type: Micro-FCPGA478<br>Front side bus: 533/800 MHz   |
| <b>Memory</b>               | Two DDRII 533/667MHz DIMM up to 3GB with dual channel Interleaved mode   |
| <b>Chipset</b>              | Intel GME965 & ICH8-M(82801HBM)  |
| <b>Real Time Clock</b>      | Chipset integrated RTC with onboard lithium battery  |
| <b>Watchdog Timer</b>       | Generates a system reset with internal timer for 1min/s ~ 255min/s   |
| <b>Power Management</b>     | ACPI 1.0 compliant, supports power saving mode   |
| <b>PCI Enhanced IDE</b>     | One 44-pin UltraATA33 IDE interface supports up to 2 ATAPI devices   |
| <b>Serial ATA Interface</b> | 3 x serial ATAll interface with 300MB/s transfer rate  |
| <b>VGA Interface</b>        | Intel integrated extreme GMA X3100(Graphic Media Accelerator) Technology   |
| <b>Video Memory</b>         | Up to 384MB shared with system memory  |
| <b>LVDS interface</b>       | Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply  |
| <b>DVI Interface</b>        | Two Chrontel CH7307C DVI transmitter with onboard 26-pin DVI interface   |
| <b>Audio Interface</b>      | Intel integrated ICH8-M with Realtek ALC888 HD Audio   |
| <b>LAN Interface</b>        | Two Intel 82573L Gigabit LAN   |
| <b>Solid State Disk</b>     | IDE supports 44-Pin DiskOnModule with +5V/+3.3V power supply,<br>One Compact Flash Type II   |
| <b>GPIO interface</b>       | Onboard programmable 8-bit Digital I/O interface   |
| <b>Extended Interface</b>   | One PCI slot, Two Mini PCI socket to support Mini PCI Type IIIA  |
| <b>Internal I/O Port</b>    | 1 x RS232/422/485, 1 x slim FDD port, 1 x GPIO port, 1 x Parallel Port,<br>4 x USB ports, 1 x IrDA, 1 x IDE, 1 x LVDS , 1 x LCD inverter connector,<br>2 x DVI, 1 x HDTV, 1 x Front panel Audio connector and 1 x CDIN connector |
| <b>External I/O Port</b>    | 1 x PS/2 Keyboard/Mouse Port, 2 x RJ45 LAN ports, 1 x DB15 VGA port,<br>4 x USB2.0 ports, 2 x IEEE1394 port, 1 x RS232 port , 7.1 Channel Audio<br>Output, 1 x SPDIF connector   |
| <b>Power Requirement</b>    | Standard 20-pin ATX power supply<br>or 9~24V full range DC Input ( 8~30V operative)  |
| <b>Dimension</b>            | 170mm x 170mm  |
| <b>Temperature</b>          | Operating within 0~60 centigrade<br>Storage within -20~85 centigrade   |

## Ordering Code

|                  |   |
|------------------|---|
| <b>LV-679D</b>   | Onboard CRT, LVDS, HDTV, Intel Gigabit LAN, USB2.0, PCI, Mini-PCI, GPIO Port, 1394, IrDA, Slim FDD, Parallel Port, RS232/422/485, SATA, HD Audio, <b>1 x DVI</b>        |
| <b>LV-679D2C</b> | Onboard CRT, LVDS, HDTV, Intel Gigabit LAN, USB2.0, PCI, Mini-PCI, GPIO Port, 1394, IrDA, Slim FDD, Parallel Port, RS232/422/485, SATA, HD Audio, <b>2 x DVI and CF</b> |

For further product information please visit the website at <http://www.commell.com.tw>

### Taiwan Commate Computer Inc.

8F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website: [www.commell.com.tw](http://www.commell.com.tw)

FAX: +886-2-26963911

E-mail: [info@commell.com.tw](mailto:info@commell.com.tw)



Stage For Your Success